



MATERIAL SAFETY DATA SHEET

Product Name: Rapid Evaporation, Degreasing & Decarbonising Fluid

Page: 1 of 5

This revision issued: December, 2009

Section 1 - Identification of Chemical Product and Company

Company Name & Address

Cyndan Chemicals
1/7 Jubilee Ave
Warriewood NSW 2102

Telephone: (02) 9998 5688 (Office hours)

Email: info@cyndan.com.au

Web: www.cyndan.com.au

Substance: Blend of ingredients.
Trade Name: **Rapid Evaporation, Degreasing & Decarbonising Fluid**
Product Use: Degreasing and decarbonising fluid in industrial applications.
Creation Date: **December, 2009**
This version issued: **December, 2009** and is valid for 5 years from this date.

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. Xi, Irritating. N, Dangerous to the environment. F+, Highly Flammable. Hazardous according to the criteria of SWA.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

Risk Phrases: R11, R67, R36/37/38, R50/53. Highly flammable. Vapours may cause drowsiness and dizziness. Irritating to eyes, respiratory system and skin. Very toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment.

Safety Phrases: S2, S16, S23, S29, S33, S37, S38, S60, S61, S24/25. Keep out of reach of children. Keep away from sources of ignition - No smoking. Do not breathe vapours. Do not empty into drains. Take precautionary measures against static discharges. Wear suitable gloves. In case of insufficient ventilation, wear suitable respiratory equipment. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Refer to special instructions/Safety Data Sheets. Avoid contact with skin and eyes.

SUSDP Classification: None allocated.

ADG Classification: Class 3: Flammable liquids.

UN Number: 1993, FLAMMABLE LIQUID, N.O.S.

Emergency Overview

Physical Description & colour: Clear, slightly yellowish liquid.

Odour: Clean citrus fragrance.

Major Health Hazards: No major health hazards. Irritating to eyes, respiratory system and skin, vapours may cause drowsiness and dizziness.

Potential Health Effects

Persons sensitised to sensitisers identified in Section 11 should avoid contact with this product.

Inhalation:

Short term exposure: Available data indicates that this product is not harmful. However product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased.

Long Term exposure: Vapours may cause drowsiness and dizziness.

Skin Contact:

Short term exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short term exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms

should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short term exposure: Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: Isopropanol is Class 3 - unclassifiable as to carcinogenicity to humans.

D-limonene is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Isopropanol		67-63-0 30	983	1230
d-limonene		5989-27-5 to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Suitable extinguishing media are carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

MATERIAL SAFETY DATA SHEET

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: 12-15°C
Upper Flammability Limit: No data.
Lower Flammability Limit: No data.
Autoignition temperature: No data.
Flammability Class: Flammable

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include Viton, Nitrile, butyl rubber, PE/EVAL, Responder. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure limits	TWA (mg/m ³)	STEL (mg/m ³)
Isopropanol	983	1230

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: Viton, nitrile, butyl rubber, PE/EVAL, Responder.

MATERIAL SAFETY DATA SHEET

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where product is being used.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Clear, slightly yellowish liquid.
Odour:	Clean citrus fragrance.
Boiling Point:	Begins boiling at about 80°C at 100kPa
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	30% (IPA content).
Vapour Pressure:	No data.
Vapour Density:	No data.
Specific Gravity:	No data.
Water Solubility:	Partially soluble.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water distribution:	No data
Autoignition temp:	No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents, porous materials such as zeolites and similar mineral products, rags.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

Section 11 - Toxicological Information

There is no data to hand indicating any particular target organs.

D-limonene is Classed by SWA as a potential sensitiser by skin contact.

Toxicity: IMMEDIATE (ACUTE) EFFECTS, Isopropanol:

Oral LD₅₀ (rat): 5045 mg/kg Inhalation LC₅₀ (rat): 16,000 ppm/8 hours

Skin LD₅₀ (rabbit): 12,800 mg/kg Skin Irritation (rabbit): 500 mg - mild

Eye Irritation (rabbit): 10 mg - moderate: 100 mg - severe

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

Subchronic Inhalation (rat): TCLo 5000 ppm/6 hr/day for 90 days (intermittent) caused a change in motor activity.

Chronic Inhalation (rat): TCLo 2500 ppm/6 hr/day for 2 years (intermittent) caused changes in liver and bladder weight and changes in urine composition.

OTHER DATA: Some very rare cases of skin hypersensitivity to Isopropanol have been reported. However, these cases do not at this time warrant Isopropanol to be classed as a sensitiser.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Isopropanol	Conc>=20%: Xi; R36
D-limonene	Conc>=20%: Xi; R38; R43

Section 12 - Ecological Information

Very toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment. This product is not readily biodegradable. However, likely to degrade slowly in the soil or water.

For Isopropanol: Biodegradation: 58% theoretical BOD, 5 days at 20°C - Relatively biodegradable.

Bioconcentration: Not expected to bioaccumulate in aquatic organisms based on low octanol/water partition coefficient.

Acute Toxicity (fathead minnow): LC₅₀ 10.4 g/L /96 hr.

MATERIAL SAFETY DATA SHEET

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

Section 14 - Transport Information

ADG Code: 1993, FLAMMABLE LIQUID, N.O.S.

Hazchem Code: 3YE

Special Provisions: 274

Limited quantities: ADG 7 specifies a Limited Quantity value of 1 L for this class of product.

Dangerous Goods Class: Class 3: Flammable liquids.

Packaging Group: II

Packaging Method: P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSDP	Standard for the Uniform Scheduling of Drugs & Poisons
UN Number	United Nations Number

CONTACT POINT

TELEPHONE (Business hours): (02) 9998 5688 Fax: (02) 9999 2086

National Poisons Information Centre: Dial 13 1126 (from anywhere in Australia)

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER SHOULD READ THIS MSDS AND CONSIDER THE INFORMATION IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE INCLUDING IN CONJUNCTION WITH OTHER PRODUCTS. IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY. THE RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the SWA document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]
Copyright © Kilford & Kilford Pty Ltd, December, 2009.

<http://www.kilford.com.au/> Phone (02)9251 4532

MATERIAL SAFETY DATA SHEET