



MATERIAL SAFETY DATA SHEET

Product Name: Cyndan Citrus Oil Formulation

Page: 1 of 5

This revision issued: August, 2010

Section 1 - Identification of Chemical Product and Company

Company Name & Address

Cyndan Chemicals
1/7 Jubilee Ave
Warriewood NSW 2102

Telephone: (02) 9998 5688 (Office hours)

Email: info@cyndan.com.au

Web: www.cyndan.com.au

Substance: Major ingredient is a terpene hydrocarbon.
Trade Name: **Cyndan Citrus Oil Formulation**
Product Use: General purpose solvent/cleaner.
Creation Date: **November, 2005**
This version issued: **August, 2010** and is valid for 5 years from this date.

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of SWA Australia.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

Risk Phrases: R10, R38, R43, R66. Flammable. Irritating to skin. May cause sensitisation by skin contact. Repeated exposure may cause skin dryness or cracking.

Safety Phrases: S16, S28, S39, S24/25, S36/39. Keep away from sources of ignition - No smoking. After contact with skin, wash immediately with plenty of soap and water. Wear eye/face protection. Avoid contact with skin and eyes. Wear suitable protective clothing and eye/face protection.

SUSDP Classification: None allocated.

ADG Classification: Class 3 (FLAMMABLE LIQUID, N.O.S.)

UN Number: 1993

Emergency Overview

Physical Description & colour: Clear, colourless liquid.

Odour: Strong citrus odour.

Major Health Hazards: skin irritant, possible skin sensitiser.

Potential Health Effects

Note: sensitisation to ingredients such as d-limonene occurs in only a small percentage of persons, but those who are sensitised may show severe reactions. Most people may use this product in complete safety, however those sensitised to d-limonene should avoid contact with this product.

Inhalation

Short term exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short term exposure: Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can be severe. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short term exposure: This product may cause eye irritation when present at high vapour pressures; for example when heated or in enclosed spaces. In addition product may be irritating to eyes, but is unlikely to cause anything more than mild transient discomfort.

Long Term exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short term exposure: Significant oral exposure is considered to be unlikely. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: D-limonene is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
D-limonene	5989-27-5	>80	not set	not set
Non hazardous surfactants	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Skin Contact: Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelid(s) open. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.

Ingestion: If product is swallowed or gets in mouth, wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and and breathing apparatus.

Flash point: Approx 50°C

Upper Flammability Limit: 6.1%

Lower Flammability Limit: 0.7% (d-limonene)

Autoignition temperature: No data.

Flammability Class: Flammable

MATERIAL SAFETY DATA SHEET

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Can be slippery on floors, especially when wet. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Exothermic reactions leading to spontaneous combustion are possible when products of this type are absorbed onto porous materials such as zeolites, other mineral derived products, and even rags. Therefore, avoid the use of those materials and seek specialist advice in large scale cleanup processes.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 10000kg or L of Dangerous Goods of Packaging Group III, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits

TWA (mg/m³)

STEL (mg/m³)

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

Eye Protection: Eye protection such as protective glasses or goggles should be worn when there is a chance of irritant levels of vapours being generated. However, it would be better to remove the vapours or avoid their generation.

Skin Protection: If you believe you may have a sensitisation to this product or any of its declared ingredients, you should prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being used.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Clear, colourless liquid.

MATERIAL SAFETY DATA SHEET

Odour:	Strong citrus odour.
Boiling Point:	Approx 150°C at 100kPa
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	No specific data. Expected to be low at 100°C.
Vapour Pressure:	No data.
Vapour Density:	No data.
Specific Gravity:	0.85-0.90
Water Solubility:	Emulsifiable.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water distribution:	No data
Autoignition temp:	No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

See Section 6 of this MSDS regarding reactivity with porous materials and rags.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents, porous materials such as zeolites and similar mineral products, rags.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water.

Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

D-limonene is Classified by SWA as a potential sensitiser by skin contact.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
D-limonene	Conc>=20%: Xi; R38; R43

Section 12 - Ecological Information

This product is only slowly biodegradable. It may be harmful to aquatic organisms. Please do not dispose to sewer.

Section 13 - Disposal Considerations

Disposal: There are many pieces of legislation covering waste disposal and they differ in each state and territory, so each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. The Hierarchy of Controls seems to be common - the user should investigate: Reduce, Reuse, and Recycle and only if all else fails should disposal be considered. Note that properties of a product may change in use, so that the following suggestions may not always be appropriate. The following may help you in properly addressing this matter for this product. This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

Section 14 - Transport Information

ADG Code: 1993, FLAMMABLE LIQUID, N.O.S.

Hazchem Code: 3Y

Special Provisions: 223, 274

Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

Dangerous Goods Class: Class 3, Flammable liquids.

Packaging Group: III

Packaging Method: P001, IBC03, LP01

MATERIAL SAFETY DATA SHEET

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition
AICS	Australian Inventory of Chemical Substances
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
SWA	Safe Work Australia, formerly ASCC and NOHSC
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSDP	Standard for the Uniform Scheduling of Drugs & Poisons
UN Number	United Nations Number

TELEPHONE (Business hours): (02) 9998 5688 Fax: (02) 9999 2086

National Poisons Information Centre: Dial 13 1126 (from anywhere in Australia)

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER SHOULD READ THIS MSDS AND CONSIDER THE INFORMATION IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE INCLUDING IN CONJUNCTION WITH OTHER PRODUCTS. IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY. THE RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the SWA document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2001(2003)]
Copyright © Kilford & Kilford Pty Ltd, August, 2010.

<http://www.kilford.com.au/> Phone (02)9251 4532

MATERIAL SAFETY DATA SHEET