

CAUTION
KEEP OUT OF REACH OF CHILDREN

DISLODGE

Degreasing Concentrate

780g/L LIQUID HYDROCARBON

Cyndan Dislodge is a degreasing concentrate that when added to other solvents, makes them water soluble and more effective. Cyndan Dislodge may be used undiluted. When diluted with other solvents, dislodge increases the penetration and cleaning effects of the solvent and allows them to wash cleanly away with water. This results in a totally clean surface.

DIRECTIONS FOR USE:

- For cleaning motors, running gear etc. which have heavy grease and oil build up dilute Cyndan Dislodge with 3 parts of solvent (e.g. kerosene) Spray mix onto the area, brush and rinse with a pressure hose. Brushing is not always essential. This depends on the amount of build up.
- Cyndan Dislodge may be diluted with 10 parts solvent if the build up is minimal.
- Parts may be soaked in Cyndan Dislodge at any concentration, depending on the job required.
- Pre delivery wax may be removed from vehicles with Cyndan Dislodge. A very weak solution should be tested first (e.g. 1 part Dislodge to 20 parts solvent) Test on an inconspicuous area first to confirm that there is no paint damage. Apply with cloth or spray and wipe, rinse vehicle with a pressure hose.
- To remove grease and oil from concrete floors etc. Use Cyndan Dislodge diluted with 3 parts of solvent, spray the floor with the solution, scrub and rinse with a pressure hose.

FIRST AID:

If poisoning occurs, contact a doctor or Poisons Information Centre on 13 11 26 (Australia); 0800 764 766 (New Zealand). If swallowed, DO NOT induce vomiting, give a glass of water.

