



MATERIAL SAFETY DATA SHEET

Product Name: Cyndan Electroclean

Page: 1 of 5

This revision issued: August, 2010

Section 1 - Identification of Chemical Product and Company

Company Name & Address

Cyndan Chemicals

1/7 Jubilee Ave

Warriewood NSW 2102

Telephone: (02) 9998 5688 (Office hours)

Email: info@cyndan.com.au

Web: www.cyndan.com.au

Substance: Liquid hydrocarbon with hydrocarbon propellant.
Trade Name: **Cyndan Electroclean**
Product Use: Degreasing and cleaning of electrical circuit boards.
Creation Date: **April, 2004**
This version issued: **August, 2010**

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Not classified as hazardous according to the criteria of SWA Australia.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

Risk Phrases: R11, R66. Highly flammable. Repeated exposure may cause skin dryness or cracking.

Safety Phrases: S16, S24, S29, S39. Keep away from sources of ignition - No smoking. Avoid contact with skin. Do not empty into drains. Wear eye/face protection.

SUSDP Classification: None allocated.

ADG Classification: Class 2.1, Sub risk 3 (Flammable liquid)

UN Number: 1950

Emergency Overview

Physical Description & colour: Clear colourless liquid.

Odour: Characteristic solvent odour.

Major Health Hazards: no significant risk factors have been found for this product.

Potential Health Effects

Inhalation

Short term exposure: Available data indicates that this product is not harmful. In addition product is unlikely to cause any discomfort or irritation.

Long Term exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short term exposure: Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

Long Term exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short term exposure: Exposure via eyes is considered to be unlikely. If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

Long Term exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short term exposure: Significant oral exposure is considered to be unlikely. This product is unlikely to cause any irritation problems in the short or long term.

Long Term exposure: No data for health effects associated with long term ingestion.

MATERIAL SAFETY DATA SHEET

Issued by: Cyndan Chemicals

Phone: (02) 9998 5688

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Isohexane	107-83-5	60-80	not set	not set
Other non hazardous ingredients	secret	approx 1	not set	not set
Butane	106-97-8	to 100	1900	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures**General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Skin Contact: Irritation is unlikely. However, if irritation does occur, flush with lukewarm, gently flowing water for 5 minutes or until chemical is removed. If in doubt obtain medical advice.

Eye Contact: Flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelid(s) open. Obtain medical advice if irritation becomes painful or lasts more than a few minutes.

Ingestion: First aid is not generally required. If in doubt contact a Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and and breathing apparatus.

Flash point: Isohexane -32°C

Upper Flammability Limit: 7%

Lower Flammability Limit: 1.2% (Isohexane)

Autoignition temperature: No data.

Flammability Class: Flammable

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. As a minimum, wear overalls, goggles and gloves. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type AX cartridge, suitable for low boiling point organic compounds. See manufacturer's specifications for detailed specifications.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Take suitable precautions eg use of non-sparking equipment to avoid creating sparks or flames which may ignite the spilled material. Leaking gases may form an explosion hazard. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled

MATERIAL SAFETY DATA SHEET

containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you probably require a license to do so. If you have any doubts, we suggest you contact your licensing authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Butane	1900	not set

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Eye protection such as protective glasses or goggles should be worn when there is a chance of irritant levels of vapours being generated. However, it would be better to remove the vapours or avoid their generation.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when skin exposure is likely. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should be provided near to where this product is being used.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Clear colourless liquid.
Odour:	Characteristic solvent odour.
Boiling Point:	Isohexane boils about 60°C at 100kPa
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	Completely volatile at 100°C.
Vapour Pressure:	10kPa at 2°C (Isohexane)
Vapour Density:	No data.
Specific Gravity:	Isohexane about 0.65 at 20°C
Water Solubility:	Negligible.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water distribution:	No data
Autoignition temp:	No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed. Store in the closed original container in a dry, cool, well-ventilated area out of direct sunlight.

MATERIAL SAFETY DATA SHEET

Incompatibilities: oxidising agents.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product is unlikely to undergo polymerisation processes.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient

Risk Phrases

No ingredient mentioned in the HSIS database is present in this product at hazardous concentrations.

Section 12 - Ecological Information

This product is biodegradable. It will evaporate readily and not accumulate in the soil or water or cause long term problems.

Section 13 - Disposal Considerations

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Do not puncture or incinerate cans, even when empty. Please do NOT dispose into sewers or waterways.

Section 14 - Transport Information

ADG Code: 1950, AEROSOLS

Hazchem Code: 2YE

Special Provisions: 63, 190, 277

Limited quantities: ADG 7 specifies a Limited Quantity value of 1000mL for this class of product.

Dangerous Goods Class: Class 2.1, Flammable gases.

Sub Risk: Class 3 (Flammable liquid)

Packaging Group: Not set

Packaging Method: P003

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are to be found in the public AICS Database.

Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition
AICS	Australian Inventory of Chemical Substances
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
SWA	Safe Work Australia, formerly ASCC and NOHSC
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSDP	Standard for the Uniform Scheduling of Drugs & Poisons
UN Number	United Nations Number

MATERIAL SAFETY DATA SHEET

TELEPHONE (Business hours): (02) 9998 5688

Fax: (02) 9999 2086

National Poisons Information Centre:

Dial 13 1126 (from anywhere in Australia)

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER SHOULD READ THIS MSDS AND CONSIDER THE INFORMATION IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE INCLUDING IN CONJUNCTION WITH OTHER PRODUCTS. IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY. THE RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the SWA document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [SWA:2001(2003)]

Copyright © Kilford & Kilford Pty Ltd, August, 2010.

<http://www.kilford.com.au/> Phone (02)9251 4532

MATERIAL SAFETY DATA SHEET