



# MATERIAL SAFETY DATA SHEET

Product Name: Graffiti Armour Solvent

Page: 1 of 5

This issued: November, 2011

## Section 1 - Identification of Chemical Product and Company

### Company Name & Address

Cyndan Chemicals  
1/7 Jubilee Ave  
Warriewood NSW 2102

Telephone: (02) 9998 5688 (Office hours)

Email: [info@cyndan.com.au](mailto:info@cyndan.com.au)

Web: [www.cyndan.com.au](http://www.cyndan.com.au)

**Substance:** Petroleum distillate.  
**Trade Name:** **Graffiti Armour Solvent**  
**Product Use:** Industrial Solvent.  
**Creation Date:** **November, 2011**  
**This version issued:** **November, 2011** and is valid for 5 years from this date.

## Section 2 - Hazards Identification

### Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of SWA Australia.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

**Risk Phrases:** R10, R37, R65, R66, R67.

**Safety Phrases:** S2, S23, S24, S61, S62

**SUSDP Classification:** 5

**ADG Classification:** Class 3

**UN Number:** 1268

### Emergency Overview

**Physical Description & colour:** Clear, colourless liquid.

**Odour:** Mild hydrocarbon odour.

**Major Health Hazards:** Irritating to respiratory system.

### Potential Health Effects

#### Inhalation

**Short term exposure:** Significant inhalation exposure is considered to be unlikely. Available data indicates that this product is not harmful. However product is believed to be mildly irritating, but unlikely to cause anything more than mild discomfort.

**Long Term exposure:** No data for health effects associated with long term inhalation.

#### Skin Contact:

**Short term exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

**Long Term exposure:** No data for health effects associated with long term skin exposure.

#### Eye Contact:

**Short term exposure:** Exposure via eyes is considered to be unlikely. This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

**Long Term exposure:** No data for health effects associated with long term eye exposure.

#### Ingestion:

**Short term exposure:** Significant oral exposure is considered to be unlikely. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

**Long Term exposure:** No data for health effects associated with long term ingestion.

#### Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** See the IARC website for further details.

### Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Solvent naphtha.	64742-95-6	100	100	PEAK

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### Section 4 - First Aid Measures

#### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

**Inhalation:** If irritation is experienced, remove victim from area and allow to breath fresh air. If irritation persists, call a doctor or poisons information centre.

**Skin Contact:** Gently blot away excess liquid. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately.

**Ingestion:** If product is swallowed or gets in mouth, wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

### Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards:** This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Hydrocarbon resistant foam is the preferred firefighting medium but, if it is not available, fine water spray can be used. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

**Flash point:** 50°C

**Upper Flammability Limit:** 7%

**Lower Flammability Limit:** 2%

**Autoignition temperature:** 507°C

**Flammability Class:** Flammable

### Section 6 - Accidental Release Measures

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include Viton, Nitrile. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours. Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains

#### MATERIAL SAFETY DATA SHEET

or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Solvent naphtha	100	PEAK

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: Viton, nitrile.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being used.

## Section 9 - Physical and Chemical Properties:

<b>Physical Description &amp; colour:</b>	Clear, colourless liquid.
<b>Odour:</b>	Mild hydrocarbon odour.
<b>Boiling Point:</b>	185°C at 100kPa
<b>Freezing/Melting Point:</b>	Approx -58°C
<b>Volatiles:</b>	Completely volatile at 100°C.
<b>Vapour Pressure:</b>	1.3 kPa at 20°C
<b>Vapour Density:</b>	4.3
<b>Specific Gravity:</b>	0.85
<b>Water Solubility:</b>	Not soluble.
<b>pH:</b>	No data.
<b>Volatility:</b>	No data.
<b>Odour Threshold:</b>	No data.
<b>Evaporation Rate:</b>	<1
<b>Coeff Oil/water distribution:</b>	No data
<b>Autoignition temp:</b>	507°C

### MATERIAL SAFETY DATA SHEET

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

**Incompatibilities:** oxidising agents.

**Fire Decomposition:** Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## Section 11 - Toxicological Information

**Toxicity:** IMMEDIATE (ACUTE) EFFECTS:

Oral LD<sub>50</sub> (rat): >2000 mg/kg

Inhalation LC<sub>50</sub> (rat): 16,000 ppm/8 hours

Skin Irritation (rabbit): May cause moderate skin irritation but insufficient to classify.

Eye Irritation (rabbit): Low irritation to eyes.

### Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Solvent naphtha.	Conc>=40%: R10, R37, R65, R66, R67

## Section 12 - Ecological Information

Insufficient data to be sure of status.

Biodegradation: 58% theoretical BOD, 5 days at 20° C - Relatively biodegradable.

Bioconcentration: Not expected to bioaccumulate in aquatic organisms based on low octanol/water partition coefficient.

## Section 13 - Disposal Considerations

**Disposal:** Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Please do NOT dispose into sewers or waterways.

## Section 14 - Transport Information

**ADG Code:** 1268, Petroleum distillate.

**Hazchem Code:** 3[Y]

**Special Provisions:** None allocated

**Dangerous Goods Class:** Class 3, Flammable liquids.

**Packaging Group:** III

## Section 15 - Regulatory Information

**AICS:** This product was found in the public AICS Database.

## Section 16 - Other Information

**This MSDS contains only safety-related information. For other data see product literature.**

### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSDP</b>	Standard for the Uniform Scheduling of Drugs & Poisons

### MATERIAL SAFETY DATA SHEET

UN Number

United Nations Number

**TELEPHONE (Business hours): (02) 9998 5688**

**Fax: (02) 9999 2086**

**National Poisons Information Centre:**

**Dial 13 1126 (from anywhere in Australia)**

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER SHOULD READ THIS MSDS AND CONSIDER THE INFORMATION IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE INCLUDING IN CONJUNCTION WITH OTHER PRODUCTS. IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY. THE RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the SWA document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2001(2003)]