

**CAUTION** Keep out of reach of children  
Read safety directions before opening

# HEAT SHIELD

THERMAL INSULATION PAINT & WATERPROOF MEMBRANE

Cyndan Heat Shield is an advanced polymeric based thermal insulating paint, utilising a breakthrough Micro Crystal technology. It can be applied to any metal, timber and masonry surface to provide excellent thermal insulation and waterproofing properties.

## **DIRECTIONS:**

Clean entire surface adequately before application.

**ON METAL:** Apply 1 Coat of Cyndan Rust Buster as an undercoat. When dry, apply Heat Shield to the area.

**ON MASONRY:** Apply products directly onto the masonry surface

**ON TIMBER:** Apply product directly to the timber surface (sanding preparation recommended).

For air assisted spray application, 2 liberal coats is recommended or using a double pass.

By roller 1 thick coat or 2 coats wet on dry is recommended.

Coverage by spray 12 m<sup>2</sup> per litre per coat. By roller application 10m<sup>2</sup> per litre per coat.

Curing time = 24 hours before allowing to get wet. 48 hours for full cure.

**SAFETY:** Avoid contact with eyes.

**FIRST AID:** If swallowed, do NOT induce vomiting, give a glass of water and seek medical attention. Contact the Poisons Information Centre (13 11 26 Australia; 0800 764 766 New Zealand). If in eyes, hold eyelids open and flush with water for at least 15 minutes.

Batch #:

20L

\* Trademark



Cyndan Chemicals 1/7 Jubilee Avenue Warriewood NSW 2102 AUSTRALIA ph +61 2 9998 5688 www.cyndan.com.au