

CAUTION Keep out of reach of children
Read safety directions before opening

METAL PROTECTIVE COATING FOR THE PROTECTION OF METALS FROM CORROSION

CYNDAN* Metal Protective Coating is ideally suited to any metals which require protection from corrosive elements. CYNDAN* Metal Protective Coating is formulated for industrial indoor and outdoor protection. The resultant protective coating is not tacky to touch, therefore the protected equipment can be utilised and handled.

DIRECTIONS:

Ensure the objects to be protected are liberally coated either by spray, dip or brush methods. Allow the coating to cure. The time required will vary with the climatic conditions. However, 20 minutes is normally adequate. It is advisable to attempt to displace any moisture. The use of CYNDAN* MOISTURE STRIPPER is ideal for this operation (Please see your CYNDAN* Representative for a demonstration). CYNDAN* Metal Protective Coating can be removed by a solvent such as CYNDAN* DISLODGE. This is done by rubbing the protected object with CYNDAN* DISLODGE. Clean the application equipment with CYNDAN* DISLODGE.

SAFETY: Avoid contact with eyes.

FIRST AID: If swallowed, do NOT induce vomiting, give a glass of water and seek medical attention. Contact the Poisons Information Centre (13 11 26 Australia; 0800 764 766 New Zealand). If in eyes, hold eyelids open and flush with water for at least 15 minutes.

Batch #:

* Trademark



9 343310 005930

Cyndan Chemicals 1/7 Jubilee Avenue Warriewood NSW 2102 AUSTRALIA ph +61 2 9998 5688 www.cyndan.com.au