

**CAUTION** Keep out of reach of children  
Read safety directions before opening



# SILACOAT

LUBRICATING RELEASE AGENT AND PROTECTANT

UN 1993 HAZCHEM CODE 3Y PACKAGING GROUP III

CYNDAN\* SILACOAT is a multi-purpose product and may be used by industry to prevent bonding of materials or for lubricating. CYNDAN\* SILACOAT may also be used in the motor vehicle industry for detailing as it protects, nourishes and beautifies vinyl, leather, rubber and plastics.

## DIRECTIONS:

Do Not Swallow. CYNDAN\* SILACOAT may be applied by a spray, mop, brush, dip or wiping action. CYNDAN\* SILACOAT dries quickly leaving a film of protection. When used as a release agent CYNDAN\* SILACOAT should be tested to determine suitability.

**FOR THE PROTECTION OF STAINLESS STEEL** Silacoat has found great success in the protection of all stainless steel, architectural, marine etc. The process requires first the removal of any contaminants, rusting or tea staining. This is best achieved with either Cyndan Stainless Steel Cleaner which is a liquid or Cyndan Cream Cleanser which is a paste. The application will determine the product required, please consult your Cyndan representative for details.

The next step is to spray the Silacoat liberally over the surface to be protected. Remove excess with an absorbent rag. This will allow several months protection depending on the environment.

**SAFETY:** Avoid contact with eyes.

**FIRST AID:** If swallowed, do NOT induce vomiting, give a glass of water and seek medical attention. Contact the Poisons Information Centre (13 11 26 Australia; 0800 764 766 New Zealand). If in eyes, hold eyelids open and flush with water for at least 15 minutes.

Batch #:



\* Trademark

Cyndan Chemicals 1/7 Jubilee Avenue Warriewood NSW 2102 AUSTRALIA ph +61 2 9998 5688 [www.cyndan.com.au](http://www.cyndan.com.au)

9 343310 008351