

POISON Keep out of reach of children
Read safety directions before opening



POISON

6

SUPERB STRIPPING FORMULA

Contains: 524g/L Methylene Chloride, 412g/L Cresylic Acid

UN 2922 HAZCHEM CODE 2XE PACKAGING GROUP III

CORROSIVE

8

For the removal of Paint, Powder Coatings, Grease, Oils and Carbons

DIRECTIONS:

To get the best and most economical results with CYNDAN* SUPERB STRIPPING FORMULA a metal tank should be filled with the CYNDAN* SUPERB STRIPPING FORMULA and a 5cm (or 2 inch) water seal added. The water when added will float on the top of the CYNDAN* SUPERB STRIPPING FORMULA preventing the escape of the valuable evaporative solvents. The parts to be cleaned should be fully submerged and left until the carbon, grease and paint, etc. are removed. Air drying is preferred. The time required will vary on the amount of soiling. CYNDAN* SUPERB STRIPPING FORMULA is safe on most metals. Testing should take place on weaker alloys and sensitive cast harden materials, i.e. cam followers, tappets etc.

SAFETY:

Corrosive. Avoid contact with eyes and skin. Wear protective clothing, gloves and eye protection.

FIRST AID:

If swallowed, do NOT induce vomiting, give a glass of water and seek medical attention. Contact the Poisons Information Centre (13 11 26 Australia; 0800 764 766 New Zealand). If in eyes, hold eyelids open and flush with water for at least 15 minutes. If skin contact occurs, remove contaminated clothing and rinse for 15 minutes with soap and water. Ensure clothing is washed thoroughly before using again.

Batch #:

* Trademark



9 343310 009617

Cyndan Chemicals 1/7 Jubilee Avenue Warriewood NSW 2102 AUSTRALIA ph +61 2 9998 5688 www.cyndan.com.au