

**CAUTION** Keep out of reach of children  
Read safety directions before opening

## TOP COAT RESILIENT HIGH GLOSS FLOOR COATING

Takes advantage of new technology with a new complex blend of acrylic polymers that result in a long life, hard wearing, high gloss floor coating. NB: THIS PRODUCT CAN BE DILUTED WITH ONE PART WATER IF A LOW COST COATING IS REQUIRED. Otherwise for the very best finish use as supplied.

### **DIRECTIONS:**

Saturate an applicator with Cyndan Top Coat and apply an even coat to the floor, applying in one direction. Allow to dry for 10-20 minutes (depending on the atmospheric conditions). Apply a second coat in the opposite direction. If necessary apply third coat in the original direction. Use two to three liberal even coats for areas of extreme wear and allow to cure. Use only on clean, sealed surfaces.

Cyndan Top Coat can be used as a sealer by premixing with 2 parts water.

For maintenance, clean the coated floor with Cyndan Cleans All or Cyndan Deoda-Clean. Heavy traffic areas can be re-coated without stripping.

**SAFETY:** Avoid contact with eyes.

**FIRST AID:** If swallowed, do NOT induce vomiting, give a glass of water and seek medical attention. Contact the Poisons Information Centre (13 11 26 Australia; 0800 764 766 New Zealand). If in eyes, hold eyelids open and flush with water for at least 15 minutes.

Batch #:

\* Trademark



9 343310 010231

Cyndan Chemicals 1/7 Jubilee Avenue Warriewood NSW 2102 AUSTRALIA ph +61 2 9998 5688 www.cyndan.com.au